

PALACINAINTERIORS

PAINT



GALAXY ACRYLIC EPOXY 440 GLOSS ENAMEL

PRODUCT DATA

- Isocynate free topcoat
- Outstanding weather resistance with excellent colour and gloss retention
 - Resists a broad range of corrosive and marine atmosphere
 - Resists soil pick up, easily cleanable
 - Hard, tough, flexible and abrasion resistant
 - Cures through a wide temperature range

TYPICAL USES

• As a non-isocynate containing finish coat where an attractive appearance is required for offshore platforms, chemical plants, pulp and paper mills, petro refineries, marine equipment, ship topsides etc

CHEMICAL RESISTANCE GUIDE

Environment	Splash Spillage	Fumes & Weathering
Acidic	Yes	Yes
Alkaline	Yes	Yes
Solvents	Yes	Yes
Acidic, neutral, alkaline,	Yes	Yes
water		

PHYSICAL DATA

Finish: 440 Gloss Colour: BS 4800, RAL

Substrate: Suitable steel primed to specification

Components: 2

Curing Mechanism: Solvent release and chemical reaction between components

Volume Solids: 48%

Dry Film Thickness: 35-40 micron per coat

No. of coats: 1 coat

Calculated Coverage: 6-8m2 per Litre @ 35-50 DFT

Application Method: Airless or conventional spray, brush and roller

Mixing Ratio: 4 parts Base and 1 part Hardener **Thinner:** Galaxy Epoxy Thinner No. 911