

PALACINA INTERIORS PAINT

GALAXY 

SUPERTEX MATT TEXTURED FINISH

DESCRIPTION

Supertex Matt is a finely textured decorative and protective finish suitable for interior and exterior application. It contains a special synthetic resin base and fine aggregate to give excellent adhesion and long lasting, weather resistant finish. The resin base has been successfully tested in East Africa. It has excellent resistance to ultra violet ray attack and is non yellowing.

FINISH: Fine Textured matt.

SCOPE AND PURPOSE

Supertex matt has been formulated as a long lasting, weather resistant coating for application to new surfaces such as plaster, concrete, stone and galvanized iron; and previously painted surfaces in good condition. When used on roofs, the pale colours of Supertex Matt act as insulation against solar heat. Surfaces painted with Supertex Matt can be scrubbed without risk of damage or removal of the film.

SPREADING RATE

One coat on smooth surfaces:
3-4 square metres per litre with normal application. One coat on rough surfaces:
1.5 - 2 square metres per litre with normal application.

THINNING

Ready to apply. Use upto 5% by volume of water low profile texture.

METHOD OF APPLICATION

Roller or Hopper gun spray. Supertex Matt should be laid on. Over Rolling will cause the aggregate to pull out of the resin.

SURFACE PREPARATION

All surface must be clean, dry and free from dirt, efflorescence, loose or flaking paint.

DRYING TIME: Approximately 2 hours.

SPECIFICATION FOR USE

Porous surfaces: Surfaces which are very porous will require a sealing coat of Acrylic Undercoat Matt. This sealing coat should be followed by one or two full coats of Supertex as required. **Smooth Surface :** Apply one or two coats of Supertex Matt direct onto the surface