

PALACINA INTERIORS PAINT

GALAXY 

GALAXY VINYL MATT EMULSION

DESCRIPTION:

Galaxy Vinyl Matt Emulsion Paint is based on an Acrylic co-polymer emulsion to provide a tough yet flexible finish. It is made with very high quality speciality pigments and various functional extenders with selected coalescing solvents to produce continuous film surfaces.

FINISH: Matt

SCOPE AND PURPOSE:

Galaxy vinyl matt emulsion provides a reasonably tough, durable and easily washable coating for walls and ceilings. It can be scrubbed without much risk of damage or removal of the film. It is equally suitable for both inside and outside uses.

THINNING:

Can be thinned with water if necessary.

METHOD OF APPLICATION:

Supplied ready for use and may be applied by brush, roller or spray. Application is very easy and does not show up lap or brush marks. Contents should be stirred well before use.

SURFACE PREPARATION:

All surfaces must be clean, dry and free from grease and efflorescence. Any loose or flaking material must be removed from surface before application.

DRYING TIME

Surface Dry - Approximately 15 minutes under normal
Hard Dry- 4 to 6 hrs atmospheric conditions
Recoating is possible after an intercoat interval of about 2 hours.

SPECIFICATION FOR USE

New cement or plaster: On dry absorbent surfaces, the first coat may be eased for brushing or rolling with upto 10% of water. After drying apply one to two further coats as required without thinning giving sufficient intercoat interval.

PREVIOUSLY PAINTED SURFACE

If previously painted with oil paint, rub down the surface thoroughly and apply two coats of S.V.A. Emulsion paint